

# TRIOMET

---

## Stål

### **KALLDRAGEN STÅNG**

AB Triomet Stål  
Industrivägen 4  
449 44 Nol

# 4-Kantsstång

EN 10277/78  
Längd 3 - 3,5 m

Dimension	S235JRC + C	C45 + C	SS1912	SS1914
4	x			
5	x			
6	x	x	x	x
7	x		x	x
8	x	x	x	x
9	x			x
10	x	x	x	x
11			x	x
12	x	x	x	x
13	x			x
14	x			x
15	x	x	x	x
16	x		x	x
17	x			x
18	x	x	x	x
19	x			x
20	x	x	x	x
22	x	x	x	x
24	x			x
25	x	x	x	x
26	x	x		
28	x	x		x
30	x	x	x	x
32	x	x		x
35	x	x	x	x
36	x			x
38	x			
40	x	x	x	x
45	x	x	x	x
50	x	x	x	x
55	x	x	x	x
60	x	x	x	x
65	x	x		
70	x	x	x	x
75	x	x		
80	x	x	x	x
85	x	x		
90	x	x	x	x
100	x	x	x	x
120	x			

S355J2C + C, EN 10277/78  
Längd 6 - 6.5 m

8	20	25	30	35	40	45	50
55	60	70	75	80	90	100	

# 6-Kantsstång

EN 10277 / 78  
Längd 3 – 3,5 m

Dim. mm	C 35 +C	SS1912	SS1914	Dim. mm	C 35 +C	SS1912	SS1914
6			x	24	x	x	x
7		x	x	27	x	x	x
8			x	30	x	x	x
9		x	x	32	x	x	x
10	x	x	x	36	x	x	x
11		x	x	41	x	x	x
12	x	x	x	46	x	x	x
13	x	x	x	50	x	x	x
14	x	x	x	55	x	x	x
15		x	x	60	x	x	x
17	x	x	x	65	x	x	x
19	x	x	x	70	x	x	x
22	x	x	x	75		x	x

# Vinkelstång

Liksidig S235JR C + C  
EN 10277 / DIN 59370  
Längd 3 – 3,5 m

10 x 10 x 2	20 x 20 x 5	30 x 30 x 5	45 x 45 x 6	80 x 80 x 8
10 x 10 x 3	25 x 25 x 2	35 x 35 x 4	50 x 50 x 4	80 x 80 x 10
15 x 15 x 3	25 x 25 x 3	40 x 40 x 3	50 x 50 x 5	100 x 100 x 8
15 x 15 x 4	25 x 25 x 4	40 x 40 x 4	50 x 50 x 6	100 x 100 x 10
20 x 20 x 2	25 x 25 x 5	40 x 40 x 5	60 x 60 x 5	
20 x 20 x 3	30 x 30 x 3	40 x 40 x 6	60 x 60 x 6	
20 x 20 x 4	30 x 30 x 4	45 x 45 x 5	80 x 80 x 6	

Oliksidig S235JR C + C  
EN 10277 / DIN 59370  
Längd 3 – 3,5 m

20 x 10 x 3	30 x 20 x 4	40 x 20 x 5	50 x 30 x 5	80 x 40 x 6
25 x 15 x 3	40 x 20 x 3	45 x 30 x 5	60 x 30 x 5	80 x 40 x 8
25 x 15 x 5	40 x 20 x 4	50 x 30 x 4	60 x 40 x 5	100 x 50 x 10
30 x 20 x 3				

# Kalldraget Plattstål

S235JRC + C, EN 10277/78

Längd 3 -3,5 m

Bredd mm	2	3	4	5	6	8	10	12	14	15	16	18	20	25	30	35	40	50	60
8			x	x	x														
10	x	x	x	x	x	x													
12	x	x	x	x	x	x	x												
14	x	x	x	x	x	x	x	x											
15	x	x	x	x	x	x	x	x											
16	x	x	x	x	x	x	x	x											
18	x	x	x	x	x	x	x	x											
20	x	x	x	x	x	x	x	x	x	x	x	x							
22		x	x	x	x	x	x	x		x									
25	x	x	x	x	x	x	x	x		x	x	x	x						
28		x	x	x	x	x	x												
30	x	x	x	x	x	x	x	x		x	x	x	x	x					
32		x	x	x	x	x	x	x		x	x		x						
35	x	x	x	x	x	x	x	x		x	x	x	x	x	x				
36													x						
40	x	x	x	x	x	x	x	x		x	x	x	x	x	x	x			
45		x	x	x	x	x	x	x		x	x	x	x	x	x	x			
50		x	x	x	x	x	x	x		x	x	x	x	x	x	x	x		
55				x	x	x	x	x		x			x	x	x				
60		x	x	x	x	x	x	x		x	x	x	x	x	x	x	x	x	
65		x	x	x	x	x	x	x		x	x		x	x	x	x			
70			x	x	x	x	x	x		x	x	x	x	x	x	x	x	x	
75					x	x	x	x		x			x	x	x		x		
80			x	x	x	x	x	x		x	x		x	x	x	x	x	x	x
90			x	x	x	x	x	x		x	x		x	x	x	x	x	x	x
100			x	x	x	x	x	x		x			x	x	x	x	x	x	x
110				x	x	x	x	x		x			x	x	x	x	x	x	x
120				x	x	x	x	x		x	x		x	x	x	x	x	x	x
125						x	x	x		x			x						
130					x	x	x	x		x			x	x	x		x	x	x
140				x	x	x	x	x		x			x	x	x		x	x	
150				x	x	x	x	x		x			x	x	x		x	x	x
160					x	x	x	x		x			x	x	x		x		
180					x	x	x	x		x			x	x	x		x	x	x
200					x	x	x	x		x			x	x	x	x	x	x	
220						x	x	x		x			x	x	x				
250						x	x	x		x			x	x	x		x	x	
300																			x
350							x	x		x			x	x	x		x		
400								x		x			x	x	x		x		
500													x		x				

# Kalldraget Plattstål

C45 + C, EN 10277/78  
Längd 3 - 3,5 m

Bredd mm	5	6	8	10	12	15	20	25	30	40	50
20	x	x	x	x	x	x					
25	x	x	x	x	x	x	x				
30	x	x	x	x	x	x	x	x			
35	x	x	x	x	x	x	x	x			
40	x	x	x	x	x	x	x	x	x		
45		x	x	x	x	x	x	x			
50	x	x	x	x	x	x	x	x	x	x	
60	x	x	x	x	x	x	x	x	x	x	
70				x	x	x	x	x	x	x	
80				x	x	x	x	x	x	x	x
90				x		x	x	x	x	x	x
100			x	x	x	x	x	x	x	x	x
120				x		x	x				
150				x		x	x				

S355J2 C + C, EN 10277/78  
Längd 6 - 6,5 m

Bredd mm	8	10	12	15	20	25	30	40	50
20		x		x					
25		x	x	x	x				
30		x	x	x	x				
35				x	x				
40	x	x	x	x	x	x	x		
45		x							
50		x	x	x	x	x	x	x	
60		x	x	x	x	x	x	x	
70		x	x	x	x	x	x	x	
80	x	x		x	x	x	x	x	x
90		x		x	x		x		
100		x	x	x	x	x	x	x	x
120		x		x	x				
150				x					

# Kalldragen Rundstång

EN 10277/78

Längd ca 3 – 3,5 m alt. 6 – 6.5 m

mm	S235JR C + C/SH	S355J2 C + C/SH	C35/C45 + C/SH	C45 SL h6	SS1912	SS1914
3,0	x					x
4,0	x		x		x	x
5,0	x		x		x	x
6,0	x	x	x		x	x
7,0	x				x	x
8,0	x	x	x	x	x	x
9,0	x					x
10,0	x	x	x	x	x	x
11,0	x				x	
11,5						x
12,0	x	x	x	x	x	x
13,0	x				x	x
13,5						x
14,0	x	x	x	x	x	x
15,0	x	x	x	x	x	x
16,0	x	x	x	x	x	x
17,0	x				x	x
18,0	x	x	x	x	x	x
19,0	x					
19,5					x	x
20,0	x	x	x	x	x	x
21,0					x	x
22,0	x	x	x	x	x	x
23,0					x	x
24,0	x	x	x		x	x
25,0	x	x	x	x	x	x
26,0	x	x	x	x	x	x
27,0						x
28,0	x	x	x	x	x	x
30,0	x	x	x	x	x	x
32,0	x	x	x	x	x	x
34,0	x	x	x		x	x
35,0	x	x	x	x	x	x
36,0	x	x	x		x	x
38,0	x	x	x	x	x	x
40,0	x	x	x	x	x	x
42,0	x	x	x	x	x	x
45,0	x	x	x	x	x	x
46,0			x		x	x
48,0	x	x	x	x	x	x
50,0	x	x	x	x	x	x
52,0					x	x
55,0	x	x	x	x	x	x

# Kalldragen Rundstång

EN 10277/78  
Längd ca 6 - 6.5 m

Dimension mm	Seghärdningsstål 42CrMoS4+QT+SH	Sätthärdningsstål 16MnCrSS+C/SH
10		x
12		x
14		x
16		x
18		x
20	x	x
22	x	
25	x	x
26	x	
28	x	
30	x	x
35	x	x
40	x	x
45	x	x
50	x	x
55	x	x
60	x	x
65	x	x
70	x	x
80	x	x

# Kalldraget Kilstål

C45 + C, DIN 6880  
Längd 3 - 3.5 m

8 x 7	14 x 6	22 x 14	40 x 22	70 x 36
10 x 6	14 x 9	25 x 14	45 x 25	80 x 40
10 x 8	16 x 10	28 x 16	50 x 28	90 x 45
12 x 8	18 x 11	32 x 18	56 x 32	100 x 50
12 x 10	20 x 12	36 x 20	63 x 32	

C45 + C, DIN 6880  
Längd 3 - 3.5 m, 4-kant

4	6	7	8	10	12	16
---	---	---	---	----	----	----

# Kalldragen Rundstång

EN 10277/78

Längd ca 3 – 3,5 m alt. 6 – 6.5 m

mm	S235JR C + C/SH	S355J2 C + C/SH	C35/C45 + C/SH	C45 SL h6	SS1912	SS1914
56,0					X	X
60,0	X	X	X	X	X	X
65,0	X	X	X	X	X	X
70,0	X	X	X	X	X	X
75,0	X	X	X	X	X	X
80,0	X	X	X	X	X	X
85,0	X	X	X	X	X	X
90,0	X	X	X	X	X	X
95,0	X		X		X	X
100,0	X	X	X	X	X	X
105,0	X		X		X	X
110,0	X	X	X	X	X	X
115,0	X	X	X		X	X
120,0	X	X	X	X	X	X
125,0	X		X		X	X
130,0	X	X	X		X	X
140,0	X	X	X		X	X
150,0	X	X	X		X	
160,0	X	X	X		X	

**TRIOMET**  
**Stål**

Övriga stålsorter och dimensioner anskaffas på begäran.

Leveranstid ca 5-10 dagar

## Kontakta oss

Thomas Ohlén  
0303-740040  
Mob: 0702-332065  
Mail: [thomas@triomet.se](mailto:thomas@triomet.se)

Richard Ohlén  
0303-740040  
Mob: 0722-278548  
Mail: [richard@triomet.se](mailto:richard@triomet.se)

Fax: 0303-742410

### Adress

AB Triomet Stål  
Industrivägen 4  
449 44 Nol  
[www.triometstal.se](http://www.triometstal.se)